Technisches Datenblatt
Technical Data Sheet

Viton® FKM Moosgummi Rundschnur/Vierkantprofil
Viton® Fluoride Foam Rubber Round Cord/Strip

	Viton® Fluormoosgummi ***Viton® Fluoride Foam Rubber***	08.01.2026
Härte / *Hardness*	ca. / *approx.* 30° Shore A (ASTM D2240)	
Farbe / *Colour*	schwarz / *black*	
Zellart / *Cell type*	geschlossenzellig mit Haut / *closed cell with skin*	
Temperatur / *Temperature*	-20° / +200°C	
Zugfestigkeit / *Tensile Strength*	1,2 MPa (ASTM D412)	
Reißdehnung / *Elongation At Break*	>= 120% (ASTM D412)	
Druckverformrest / *Compression Set*	50% à 100°C, 24 h (ASTM D395 B1)	
Chemische Beständigkeit / *Chemical Resistance*	ölbeständig / *oil resistant*	
Andere Eigenschaften / *Other Properties*	UL94 V0 konform / *conform*	

Jederzeitige Änderungen vorbehalten.
Alle in diesem technischen Datenblatt enthaltenen Angaben stützen sich auf eine begrenzte Anzahl von Prüfungen an Normprüfkörpern aus Laborfertigung. Sie dienen nur als Anhaltspunkt und wurden vom Rohstofflieferant ohne Gewähr übernommen. Es obliegt dem Käufer, selbst zu prüfen, ob das Produkt für die vorgesehenen Anwendungen geeignet ist.

Subject to change without prior notice.
All information contained in this technical data sheet is based on a limited number of tests done on standard test specimens made by laboratory production. They are only intended as reference and were extracted without guarantee from the raw material supplier. It is the buyer's obligation to check if the product is suitable for the intended application.